

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 December 2005 (22.12.2005)

PCT

(10) International Publication Number
WO 2005/121387 A1

(51) International Patent Classification⁷: **C22F 1/18**

(21) International Application Number:
PCT/JP2005/010639

(22) International Filing Date: 3 June 2005 (03.06.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-172183 10 June 2004 (10.06.2004) JP

(71) Applicant (for all designated States except US):
YAMAHA HATSUDOKI KABUSHIKI KAISHA
[JP/JP]; 2500, Shingai, Iwata-shi, Shizuoka, 4388501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SUZUKI, Taka-
haru [JP/JP]; c/o YAMAHA HATSUDOKI KABUSHIKI
KAISHA, 2500, Shingai, Iwata-shi, Shizuoka, 4388501
(JP). ADACHI, Shuhei [JP/JP]; c/o YAMAHA HATSU-
DOKI KABUSHIKI KAISHA, 2500, Shingai, Iwata-shi,
Shizuoka, 4388501 (JP).

(74) Agent: OKUDA, Seiji; OKUDA & ASSOCIATES, 10th
Floor, Osaka Securities Exchange Bldg., 8-16, Kitahama
1-chome, Chuo-ku, Osaka-shi, Osaka 5410041 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AI, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KI,
KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,
MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ,
OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL,
SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC,
VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: TITANIUM ALLOY PART AND METHOD FOR PRODUCING THE SAME



(57) Abstract: A titanium alloy part according to the present in-
vention has a compressive stress of approximately 270 MPa or
more within a depth of about 100 μm from a surface thereof. Since
a large compressive stress exists in the area of the surface, the tita-
nium alloy part according to the present invention exhibits a high
fatigue strength.

WO 2005/121387 A1